ROUGH TERRAIN SERIES

MODEL	WORK HEIGHT	Raised Platform Height	Lowered Platform Height	O/A Width	O/A Length	Stowed Height Railings Up	Stowed Height Railings Down	% Grade- ability Ω	CAPACITY LBS. (kg) \(\Sigma\)	PLATFORM SIZE (Inside Dimension)	TRAVEL SPEED (mph)	LIFT TIME (sec) †	WEIGHT LBS. (kg) ∑
		В	I G	D	E C	K	E L	E C	TR	R I C S	5		
6826E	32' (9.7m)	26' (7.9m)	50" (1.27m)	68" (1.73m)	99.5" (2.52m)	93.5" (2.37m)	78.5" (1.99m)	30%	1200 (544kg)	57" x 84" (1.45 x 2.13m)	2 (3.2km/h)	59	5860 (2658kg)
6832E	38' (11.5m)	32' (9.7m)	55.5" (1.4m)	68" (1.73m)	99.5" (2.52m)	99" (2.51m)	84" (2.13m)	30%	1000 (454kg)	57" x 84" (1.45 x 2.13m)	2 (3.2km/h)	60	6160 (2794kg)
8831E	37' (11.3m)	31' (9.4m)	59" (1.5m)	87" (2.21m)	137.5" (3.49m)	105" (2.67m)	78.5" (1.99m)	30%	2500 (1134kg)	70" x 138" (1.78 x 3.51m)	3 (4.8km/h)	62	10575 (4797kg)
8841E	47' (14.3m)	41' (12.5m)	69" (1.75m)	87" (2.21m)	137.5" (3.49m)	114" (2.9m)	87.5" (2.22m)	30%	1500 (680kg)	70" x 138" (1.78 x 3.51m)	3 (4.8km/h)	67	12170 (5520kg)
	M I	D -	S I	ΖE	R	ο ι	I G I	4	T E	R R A	I N	S	
7127	33' (10.1m)	27' (8.2m)	60.5" (1.54m)	71.5" (1.82m)	127" (3.23m)	105.5" (2.68m)	77* (1.96m)	30%	1500 (680kg)	64" x 116.5" (1.62 x 2.96m)	3 (4.8km/h)	31	7930 (3597kg)
7135	41' (12.5m)	35′ (10.7m)	67.5" (1.71m)	71.5" (1.82m)	127" (3.23m)	112.5" (2.86m)	84" (2.13m)	30%	1000 (454kg)	64" x 116.5" (1.62 x 2.96m)	3 (4.8km/h)	38	8350 (3788kg)
	F U	L L	- S	l Z	E I	R O	U G	Н	T E	R R	A I	N S	
8831	37' (11.3m)	31' (9.4m)	59" (1.5m)	87" (2.21m)	137.5" (3.49m)	105" (2.67m)	78.5" (1.99m)	30%	2500 (1134kg)	70" x 138" (1.78 x 3.51m)	3 (4.8km/h)	58	9757 (4426kg)
8841	47' (14.3m)	41' (12.5m)	69" (1.75m)	87" (2.21m)	137.5" (3.49m)	114" (2.9m)	87.5" (2.22m)	30%	1500 (680kg)	70" x 138" (1.78 x 3.51m)	3 (4.8km/h)	56	11410 (5176kg)
9250	56′ (17.1m)	50′ (15.2m)	79" (2.01m)	92" (2.34m)	176" (4.47m)	124.5" (3.16m)	90" (2.29m)	25%	2000 (907kg)	74" x 168" (1.88 x 4.27m)	2 (3.2km/h)	67	14200 (6441kg)
9250AL	56' (17.1m)	50' (15.2m)	79" (2.01m)	92" (2.34m)	176" (4.47m)	124.5" (3.16m)	90" (2.29m)	25%	1350 (612kg)	74" x 168" (1.88 x 4.27m)	2 (3.2km/h)	67	14700 (6668kg)

† Lift times with rated load

Mid-Size Rough Terrains Full-Size Rough Terrains

6826E 6832E 8831E 8841E 7127 7135 8831 8841 9250 9250AL

- Ω Gradeability calculated with1 operator capacity
- Some capacities are reduced and overall machine weights increased when equipped with deck extensions and/or optional tires – consult factory for details

mount	00202	00022	000.2	002		7.00			,_00	7_007.1
STAN	D A	R	D	E Q	U I	P M	E N	T		
Driveable at Full Height	•	•	•	•	•	•	•	•	Up to 26'	•
DC Power (V DC)	48	48	48	48						
Battery Charger	•	•	•	•						
Dual Fuel Gas/Propane					•	•	•	•	•	•
Color Coded and Numbered Wiring System	•	•	•	•	•	•	•	•	•	•
Black Foam Filled Tires	•	•								
Grip Lug Air Filled Tires (#6)			•	•	•	•	•	•	•	Foam Filled
Slideout Engine or Battery Tray, for easy access	•	•	•	•	•	•	•	•	•	•
Tilt Alarm with Drive/Lift Cut Out	•	•	•	•	•	•	•	•	•	•
110V AC Outlet to Platform	•	•	•	•	•	•	•	•	•	•
Lanyard Attachment Points	•	•	•	•	•	•	•	•	•	•
Forklift Pockets/Lifting Lugs/Tie Downs	•	•	•	•	•	•	•	•	•	•
Folding Railings	•	•	•	•	•	•	•	•	•	•
Lockable Side Cabinets			•	•	•	•	•	•	•	•
Hydraulic Oil Level and Temperature Indicators	•	•	•	•	•	•	•	•	•	•
All Motion Alarm	•	•	•	•	•	•	•	•	•	•
Operator Horn on Platform Controller	•	•	•	•	•	•	•	•	•	•
OPTI	0 N			E Q	UI	P M	E N	Т		
Flashing Light	•	•	STD	STD	STD	STD	STD	STD	STD	STD
Liquid Cooled Diesel					•	•	•	•	•	•
Independent Leveling Outriggers			•	•	•	•	•	•	STD	STD
3500 Watt Hydraulic Generator					•	•	•	•	•	•
"Shop-Air" Line Air to Platform	•	•	•	•	•	•	•	•	•	•
4' (1.2m) Power or Manual Deck Extension f			•	•			•	•		
4.5' (1.4m) Deck Extension Δ					•	•				
5' (1.5m) Power Deck Extension	•	•							• f	•
4 Wheel Drive			•	•	•	•	•	•	•	•
Spring Loaded Half-Height Gate Entry	•	•	STD	STD	•	•	STD	STD	STD	STD
Spring Loaded Full Gate entry	•	•	•	•	STD	STD	•	•	•	•
Grip Lug Foam Filled Tires (#6F)			•	•	•	•	•	•	•	STD

The best scissor lifts in the world continue to get better.

Since its inception in 1986, Skyjack has become a global leader in the manufacturing of scissor lift work platforms. During the 90s the company grew to capture over 30% market share and remains an internationally dominant force.

In September 2002, Skyjack was purchased by Linamar Corporation (LNR, TSX) - a leading manufacturer in the automotive industry of precision-machined components, assemblies and modules. Linamar's solid balance sheet gives Skyjack increased strength and long-term stability.

Skyjack products range in working heights from 21 – 56 feet (6.4 – 17 meters) in both electric on-slab applications and internal combustion powered rough terrain models. All Skyjack's are backed up by a comprehensive, international product support network.

The new RECON division of Skyjack provides complete reconditioning programs for aging aerial work platforms, thus rounding out a total package that offers customers both new and reconditioned equipment.

Reliability, quality, service... these are the hallmarks of Skyjack. The proven commitment to excellence that has become synonymous with the Skyjack brand will continue to propel the company toward even greater success in the future.

Skyjack has manufacturing, sales and product support facilities located throughout the world. Skyjack also offers leasing, trade-in and rental/purchase programs. Call us or visit our website for more information.

This literature is for illustrative purposes only. Consult the Operating Maintenance and Parts Manual for proper procedures. Work platforms have been tested to comply with ANSI and CSA standards as interpreted by Skyjack, Inc. Specifications are subject to change without notice.





Corporate Headquarters:

Skyjack Incorporated 55 Campbell Road Guelph, Ontario N1H 1B9 Canada

Fax: 519-837-8104

North America: 800-265-2738

Overseas: +1-519-837-0888

E-mail: skyjack@skyjackinc.com

Tel: 519-837-0888

Distributed by:





BIG DECK ELECTRICS
MID SIZE RT'S
FULL SIZE RT'S







Grip Lug Air Filled Flotation Tires (#7)

 $\mathbf{\Omega}$




MID SIZE SERIES

2

When there's rough terrain on the job site, you can depend on the Mid Size Series. Powerful and compact, this series features a liquid-cooled dual fuel engine and 2-wheel drive package as standard. And the optional 4-wheel drive, outrigger package and liquidcooled diesel engine for even further versatility. Offering 30% gradeability this unit is driveable at full height on hard level surfaces. The Mid Size Series maintains a large platform capacity up to 1500lbs and has a standard rear gate for ease of loading. The 4.5' manual deck extension is standard with a power deck increasing your overall work area. Mid-size in stature,

big on production.





FULL SIZE SERIES

ш

The largest in the Rough Terrain Series, the Full Size Rough Terrains with work heights up to 56', capacities up to 2500 lbs. and 30% gradeability, offer all of the power and performance features to meet the largest of your challenges. With the exception of the SJ9250, models are driveable at full height and are equipped with a tough dual fuel engine and 2WD. Popular options include diesel engine, 4WD and dual extension decks.



œ 4 œ < S







Deck extensions increase platform



Slideout engine tray permits superior access




Universal color coded wiring for all main functions makes identification and service easy



Heavy duty lockable cabinets are both sturdy and prevent unauthorized access



110V GFI AC protected outlet to platform and lanyard attachment



Hinged rails lower stowed height for